

## SSF™ Fiber Optic Spider Breakout Kits

Part: SSF™ 6, and 12 Strand Spider Breakout Kits



Cleerline SSF™ Spider Breakout kits enable fast and easy build up of 250um fibers found in today's common micro distribution style cables. The 3.0mm color coded buffer tubes allow for the cable's overall jacket to be removed and for each 250µm fiber to simply be threaded through the corresponding colored tube. To complete, our specially designed grommet strain relief boot simplifies the assembly.

Loose tube Breakout kits are available in 6 and 12 strand configurations requirements. Works with all 250µm type cabling and industry standard connectors following 3.0mm jacket fiber termination steps.



### FEATURES

- 6 and 12 strand configurations
- Tubing colors per TIA/EIA-569-B standard
- Provides protection to any installation
- Grommet Strain relief speeds installation
- Eliminates need for patch panels
- 40in/101.5cm, or cut to length

### PART NUMBERS

PART NUMBER	PART DESCRIPTION	LENGTH
SBOK0640M250	6 STRAND	40in / 101.5cm
SBOK0640M250	12 STRAND	40in / 101.5cm

### SPECIFICATIONS

- TIA/EIA-568-B compliant
- ABS Plastic
- Hytrex furcation tubing
- 3.0mm O.D.

### APPLICATIONS

- Premise/Enterprise Networks
- Backbone, Horizontal and FTTx applications
- Data Center, Enterprise, Broadcast, Industrial
- Defense, Healthcare and Telco/MSO
- Field repair/ replacement
- LAN/WAN connections