

SpeakerCraft®



Cinema Sub

Great bass is still an integral part of any music and theater system. From the rumblings of a distant thunderstorm to the in-your-face percussive attack of a kick drum, deep, resonant bass is responsible for much of the emotional impact of any audio system. Since the volume of air movement needed to create this effect is substantial, subwoofers with dedicated enclosures and amplification have become a necessary component in all high-performance systems.

The drawback has once again been aesthetics. Subs are big and bulky. Most systems are designed with the subwoofer tucked into a corner, inevitably to be used as a plant stand. Not any more.

SpeakerCraft optimized performance by carefully designing each woofer, cabinet, and amplifier as a single system. Just like every good freestanding subwoofer is a carefully blended design of woofer, cabinet and amplifier, so to is each in wall Cinema Sub System. The final result is an in wall subwoofer that performs like its floor standing ancestors.

The three, entirely new, Cinema Subs match flawlessly to a wide variety of speaker models. In larger systems, integrating multiple subs is easy and unobtrusive. Take advantage of this opportunity to get the bass off the floor and allow it to blend into the décor with the rest of the speakers. The all-new Cinema Subs, great bass, no space.



Cinema Sub 12

- 12" Reinforced Treated Paper Cone Woofer with Dual Voice Coil
- Efficiency: 91 dB 1W/1m
- Power Handling: 250 Watts
- Impedance: 4 Ohms per Coil
- Frequency Response: 25Hz - 500kHz
- Dimensions (H x W x D): 14¹/₈" x 14¹/₈" x 3¹/₈" mm = (380 x 380 x 100)
- Cut-Out Dia. (H x W): 13³/₈" x 13³/₈" mm = (340 x 340)



AccuTune Box 12

- For Use with New Construction Installations
- Dimensions (H x W x D): 59⁷/₈" x 14³/₈" x 3¹/₄" mm = (1521 x 365 x 83)
- Cut-Out Dia. (H x W): 13³/₈" x 13³/₈" mm = (340 x 340)



Cinema Sub 10

- 10" Reinforced Treated Paper Cone Woofer with Dual Voice Coil
- Efficiency: 89 dB 1W/1m
- Power Handling: 200 Watts
- Impedance: 4 Ohms per Coil
- Frequency Response: 30Hz - 800kHz
- Dimensions (H x W x D): 13³/₈" x 13³/₈" x 3¹/₈" mm = (345 x 345 x 98)
- Cut-Out Dia. (H x W): 12¹/₈" x 12¹/₈" mm = (308 x 308)



AccuTune Box 10

- For Use with New Construction Installations
- Dimensions (H x W x D): 42³/₄" x 14³/₈" x 3¹/₄" mm = (1086 x 365 x 83)
- Cut-Out Dia. (H x W): 12¹/₈" x 12¹/₈" mm = (308 x 308)



Cinema Sub 8

- 8" Reinforced Treated Paper Cone Woofer with Dual Voice Coil
- Efficiency: 88 dB 1W/1m
- Power Handling: 150 Watts
- Impedance: 4 Ohms per Coil
- Frequency Response: 35Hz - 1000kHz
- Dimensions (H x W x D): 11¹/₂" x 11¹/₂" x 3¹/₄" mm = (292 x 292 x 95)
- Cut-Out Dia. (H x W): 10" x 10" mm = (254 x 254)



AccuTune Box 8

- For Use with New Construction Installations
- Dimensions (H x W x D): 32³/₄" x 14³/₈" x 3¹/₄" mm = (829 x 365 x 83)
- Cut-Out Dia. (H x W): 10" x 10" mm = (254 x 254)

Bass Power 250

- Mono Class A-B Subwoofer Amplifier for Cinema Sub 12
- Dual Voltage Switch and UL, CE & C-Tick Certification for US, Europe & Australia
- Includes Rack Mount Brackets
- Auto Sense Power On
- Variable Low Pass Crossover 50Hz - 150Hz
- Power Output: 250 Watts
- Impedance Handling: 4 Ohms
- Frequency Response: 30Hz - 600Hz (LFE Input)
- Dimensions (H x W x D): 3¹/₂"* x 17" x 11¹/₂"** mm = (89 x 432 x 292)



Bass Power 150

- Mono Class A-B Subwoofer Amplifier for Cinema Sub 8
- Dual Voltage Switch and UL, CE & C-Tick Certification for US, Europe & Australia
- Includes Rack Mount Brackets
- Auto Sense Power On
- Variable Low Pass Crossover 50Hz - 150Hz
- Power Output: 150 Watts
- Impedance Handling: 4 Ohms
- Frequency Response: 30Hz - 600Hz (LFE Input)
- Dimensions (H x W x D): 3¹/₂"* x 17" x 11¹/₂"** mm = (89 x 432 x 292)



* Add 1/2" for feet (13mm)

** Measurement does not include terminal connectors. Please allow another 4" for cable connections. (102mm)

- All Cinema Sub & AccuTune Box come with Limited LIFETIME Warranty

- All Electronic Components come with TWO Year Warranty

- As we incorporate design improvements, specifications may change without notice

