

220V-240V CLASSIC SERIES POWER CONDITIONERS




Furman brings together superior protection and outstanding performance in a sturdy, rack-mountable design. Classic Series Power Conditioners feature Series Multi-Stage Protection (SMP), Linear Filtering Technology (LiFT), Extreme Voltage Shutdown (EVS), and offer a new industrial design and full feature set engineered specifically for the A/V professional.



PL-8C E FEATURES



PL-PLUS C E FEATURES



PL-PRO DMC E FEATURES









FURMAN


WWW.FURMANSOUND.COM

THE POWER OF **FURMAN** TECHNOLOGY


PL-8C E FEATURES:




*Models come equipped with a 2.5M cord with IEC female to male Schuko plug.
Adapter cords are available separately. Please ask your Furman Representative
for further information about your adapter needs.



ADDITIONAL PL-PLUS C E FEATURES:



ADDITIONAL PL-PRO DMC E FEATURES:



CLASSIC SERIES REAR PANEL



PL-8C E/PL-PLUS C E REAR PANEL



PL-PRO DMC E REAR PANEL

CLASSIC SERIES SPECIFICATIONS

MAXIMUM OUTPUT CURRENT:
10 AMPS (PL-8 C E, PL-PLUS C E) - 16 AMPS (PL-PRO DMC E)

LINE CORD:
3/1.0MM AWG, 2.5M CORD W/IEC FEMALE TO 10A SCHUKO PLUG

PULL OUT LIGHTS:
TWO MULTI-LED, "SMOOTH TRACK" DIMMABLE LAMPS

BNC SOCKET W/SWITCH:
REAR RACK LAMP, 12VAC 500MA MAX (LAMP NOT INCLUDED)

OPERATING VOLTAGE:
180 TO 274 VAC

OVER VOLTAGE SHUTDOWN:
275 VAC NOMINAL

SPIKE PROTECTION MODES:
LINE TO NEUTRAL, ZERO GROUND LEAKAGE

SPIKE CLAMPING VOLTAGE:
375 VAC PEAK @3,000 AMPS

RESPONSE TIME:
1 NANOSECOND

MAXIMUM SURGE CURRENT:
6,500 AMPS

NOISE ATTENUATION:
10 DB @ 10KHZ, 40 DB @ 100KHZ, 50 DB @500 KHZ

DIMENSIONS:
482.6MM W x 266.7MM D x 44.45MM H

WEIGHT:
6 KG

POWER CONSUMPTION:
12 WATTS